



YOUSHANG SEMICONDUCTOR

**设计研发新型功率器件**

**各类小信号开关**

**中低压及高压大电流等场效应管**

0755-83047638

ysbdt@szyoushang.cn

www.szyoushang.cn



企业微信二维码



企业QQ二维码

## Features


- $BV_{CE0} > 125V$
- $I_C = 800mA$  High Continuous Collector Current

## Mechanical Data


- Case: SOT23
- Case Material: Molded Plastic, "Green" Molding Compound.  
UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish—Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208②③
- Weight 0.008 grams (Approximate)



Top View



Device Symbol



Top View  
Pin-Out

### Absolute Maximum Ratings (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	$V_{CBO}$	125	V
Collector-Emitter Voltage	$V_{CEO}$	125	V
Emitter-Base Voltage	$V_{EBO}$	5	V
Continuous Collector Current	$I_C$	800	mA
Peak Pulse Current	$I_{CM}$	1	A
Base Current	$I_B$	100	mA

### Thermal Characteristics (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)




Characteristic	Symbol	Value	Unit
Power Dissipation	$P_D$	(Note 5)	310
		(Note 6)	350
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	(Note 5)	403
		(Note 6)	357
Thermal Resistance, Junction to Leads	$R_{\theta JL}$	350	$^\circ\text{C/W}$
Operating and Storage Temperature Range	$T_J, T_{STG}$	-55 to +150	$^\circ\text{C}$

### ESD Ratings (Note 8)

Characteristic	Symbol	Value	Unit	JEDEC Class
Electrostatic Discharge—Human Body Model	ESD HBM	4000	V	3A
Electrostatic Discharge—Machine Model	ESD MM	400	V	C

- Notes:
- For the device mounted on minimum recommended pad layout FR-4 PCB with high coverage of single sided 1oz copper in still air condition; the device is measured when operating in a steady-state condition.
  - Same as note (6), except the device is mounted on 15mm x 15mm FR-4 PCB.
  - Thermal resistance from junction to solder-point (at the end of the leads).
  - Refer to JEDEC specification JESD22-A114 and JESD22-A115.

**Thermal Characteristics and Derating Information** (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)








**Electrical Characteristics** (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
<b>OFF CHARACTERISTICS</b>						
Collector-Emitter Breakdown Voltage	$BV_{CES}$	125	—	—	V	$I_C = 100\mu\text{A}$
Collector-Emitter Breakdown Voltage (Note 9)	$BV_{CEO}$	125	—	—	V	$I_{CEO} = 10\text{mA}$
Emitter-Base Breakdown Voltage	$BV_{EBO}$	7	—	—	V	$I_{EBO} = 10\mu\text{A}$
Collector-Base Cut-Off Current	$I_{CES}$	—	—	100 10	nA $\mu\text{A}$	$V_{CB} = 100\text{V}$ $V_{CB} = 100\text{V}, T_A = +150^\circ\text{C}$
Collector Cut-Off Current	$I_{CEX}$	—	—	10 75	$\mu\text{A}$ $\mu\text{A}$	$V_{CE} = 100\text{V}, V_{BE} = 0.2\text{V}, T_A = +85^\circ\text{C}$ $V_{CE} = 100\text{V}, V_{BE} = 0.2\text{V}, T_A = +125^\circ\text{C}$
Emitter-base Cut-off Current	$I_{EBO}$	—	—	100	nA	$V_{EB} = 5.6\text{V}$
<b>ON CHARACTERISTICS (Note 10)</b>						
Static Forward Current Transfer Ratio	$h_{FE}$	25 63 40	—	—	—	$I_C = 100\mu\text{A}, V_{CE} = 1\text{V}$ $I_C = 100\text{mA}, V_{CE} = 1\text{V}$ $I_C = 200\text{mA}, V_{CE} = 1\text{V}$
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	—	—	0.9	V	$I_C = 300\text{mA}, I_B = 30\text{mA}$
Base-Emitter Saturation Voltage	$V_{BE(SAT)}$	—	—	1.4	V	$I_C = 300\text{mA}, I_B = 30\text{mA}$
<b>SMALL SIGNAL CHARACTERISTICS (Note 9)</b>						
Transition Frequency	$f_T$	—	100	—	MHz	$I_C = 10\text{mA}, V_{CE} = 5\text{V}, f = 20\text{MHz}$
Output Capacitance	$C_{OBO}$	—	12	—	pF	$V_{CB} = 10\text{V}, f = 1\text{MHz}$

 Note: 9. Measured under pulsed conditions. Pulse width  $\leq 300\mu\text{s}$ . Duty cycle  $\leq 2\%$ .

**Typical Electrical Characteristics** (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)




## Package Outline Dimensions



SOT23			
Dim	Min	Max	Typ
A	0.37	0.51	0.40
B	1.20	1.40	1.30
C	2.30	2.50	2.40
D	0.89	1.03	0.915
F	0.45	0.60	0.535
G	1.78	2.05	1.83
H	2.80	3.00	2.90
J	0.013	0.10	0.05
K	0.890	1.00	0.975
K1	0.903	1.10	1.025
L	0.45	0.61	0.55
L1	0.25	0.55	0.40
M	0.085	0.150	0.110
a	0°	8°	—
All Dimensions in mm			

## Suggested Pad Layout



Dimensions	Value (in mm)
C	2.0
X	0.8
X1	1.35
Y	0.9
Y1	2.9