



YOUSHANG SEMICONDUCTOR

设计研发新型功率器件

各类小信号开关

中低压及高压大电流等场效应管

0755-83047638

ysbdt@szyoushang.cn

www.szyoushang.cn



企业微信二维码



企业QQ二维码

Features

- $BV_{CEO} > -30V$
- $I_C = -1A$ High Continuous Current
- Excellent h_{FE} Characteristics up to $-2A$
- Low Saturation Voltage $V_{CE(sat)} < -0.5V @ -1A$


Mechanical Data

- Case: SOT223
- Case Material: Molded Plastic. "Green" Molding Compound; UL Flammability Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish - Matte Tin Plated Leads; Solderable per MIL-STD-202, Method 208(3)
- Weight: 0.112 grams (Approximate)


SOT223



Top View



Device Symbol



Top View
Pin-Out

Absolute Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

| Characteristic | Symbol | Value | Unit |
|------------------------------|------------------|-------|------|
| Collector-Base Voltage | V _{CB0} | -35 | V |
| Collector-Emitter Voltage | V _{CEO} | -30 | V |
| Emitter-Base Voltage | V _{EBO} | -7 | V |
| Continuous Collector Current | I _C | -1 | A |
| Peak Pulse Current | I _{CM} | -2 | A |

Thermal Characteristics (@T_A = +25°C, unless otherwise specified.)


| Characteristic | Symbol | Value | Unit | |
|--|-----------------------------------|-------------|------|------|
| Power Dissipation | P _D | (Note 5) | 2 | W |
| | | (Note 6) | 3 | W |
| Thermal Resistance, Junction to Ambient | R _{θJA} | (Note 5) | 62.5 | °C/W |
| | | (Note 6) | 41.7 | °C/W |
| Thermal Resistance, Junction to Leads (Note 7) | R _{θJL} | 19.4 | °C/W | |
| Operating and Storage Temperature Range | T _J , T _{STG} | -55 to +150 | °C | |

ESD Ratings (Note 8)


| Characteristic | Symbol | Value | Unit | JEDEC Class |
|--|---------|-------|------|-------------|
| Electrostatic Discharge - Human Body Model | ESD HBM | 4,000 | V | 3A |
| Electrostatic Discharge - Machine Model | ESD MM | 400 | V | C |

- Notes:
5. For a device mounted with the collector lead on 25mm x 25mm 2oz copper that is on a single-sided 1.6mm FR4 PCB; device is measured under still air conditions whilst operating in a steady-state.
 6. Same as Note 5, except the device is mounted on 50mm x 50mm single sided 2oz weight copper.
 7. Thermal resistance from junction to solder-point (at the end of the collector lead).
 8. Refer to JEDEC specification JESD22-A114 and JESD22-A115.


Thermal Characteristics and Derating Information




Safe Operating Area



Derating Curve



Transient Thermal Impedance








Pulse Power Dissipation

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)


| Characteristic | Symbol | Min | Typ | Max | Unit | Test Condition |
|---|----------------------|-----------------------|------------------|--------------------|----------|---|
| Collector-Base Breakdown Voltage | BV _{CBO} | -35 | - | - | V | I _C = -100μA |
| Collector-Emitter Breakdown Voltage (Note 9) | BV _{CEO} | -30 | - | - | V | I _C = -10mA |
| Emitter-Base Breakdown Voltage | BV _{EBO} | -7 | - | - | V | I _E = -100μA |
| Collector Cut-Off Current | I _{CBO} | - | - | -100 -10 | nA uA | V _{CB} = -30V V _{CB} = -30V, T _{amb} = +100°C |
| Collector Cut-Off Current | I _{CES} | - | - | -100 | nA | V _{CE} = -30V |
| Emitter Cut-Off Current | I _{EBO} | - | - | -100 | nA | V _{EB} = -4V |
| Collector-Emitter Saturation Voltage (Note 9) | V _{CE(sat)} | - | - | -0.50 -0.75 | V | I _C = -1A, I _B = -100mA I _C = -2A, I _B = -200mA |
| Base-Emitter Saturation Voltage (Note 9) | V _{BE(sat)} | - | - | -1.25 | V | I _C = -1A, I _B = -100mA |
| Base-Emitter Turn-On Voltage (Note 9) | V _{BE(on)} | - | - | -1.0 | V | I _C = -1A, V _{CE} = -2V |
| DC Current Transfer Static Ratio (Note 9) | h _{FE} | 70 100 80 30 | - - - - | - 300 - - | - | I _C = -50mA, V _{CE} = -2V I _C = -500mA, V _{CE} = -2V I _C = -1A, V _{CE} = -2V I _C = -2A, V _{CE} = -2V |
| Transitional Frequency (Note 9) | f _T | 100 | - | - | MHz | V _{CE} = -5V, I _C = -100mA f = 100MHz |
| Output Capacitance (Note 9) | C _{obo} | - | - | 10 | pF | V _{CB} = -10V, f = 1MHz |
| Switching Times | t _{on} | - | 50 | - | ns | I _C = -500mA, V _{CC} = -10V I _{B1} = I _{B2} = -50mA |
| | t _{off} | - | 300 | - | | |

Note: 9. Measured under pulsed conditions. Pulse width ≤ 300μs. Duty cycle ≤ 2%.

Typical Electrical Characteristics (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)




Package Outline Dimensions



| SOT223 | | | |
|----------------------|-------|------|------|
| Dim | Min | Max | Typ |
| A | 1.55 | 1.65 | 1.60 |
| A1 | 0.010 | 0.15 | 0.05 |
| b | 0.60 | 0.80 | 0.70 |
| b1 | 2.90 | 3.10 | 3.00 |
| C | 0.20 | 0.30 | 0.25 |
| D | 6.45 | 6.55 | 6.50 |
| E | 3.45 | 3.55 | 3.50 |
| E1 | 6.90 | 7.10 | 7.00 |
| e | — | — | 4.60 |
| e1 | — | — | 2.30 |
| L | 0.85 | 1.05 | 0.95 |
| Q | 0.84 | 0.94 | 0.89 |
| All Dimensions in mm | | | |

Suggested Pad Layout



| Dimensions | Value (in mm) |
|------------|---------------|
| C | 2.30 |
| C1 | 6.40 |
| X | 1.20 |
| X1 | 3.30 |
| Y | 1.60 |
| Y1 | 1.60 |
| Y2 | 8.00 |