



YOUSHANG SEMICONDUCTOR

**设计研发新型功率器件**

**各类小信号开关**

**中低压及高压大电流等场效应管**

0755-83047638

ysbdt@szyoushang.cn

www.szyoushang.cn



企业微信二维码



企业QQ二维码


## Features

- $BV_{CEO} > 300V$
- $I_C$  Max. 3.5A High Continuous Collector Current
- $I_{CM}$  Max. 5A Peak Pulse Current
- Very Low Saturation Voltage  $V_{CE(sat)} < 155mV @ 1A$
- $R_{CE(sat)} = 87m\Omega$  for a Low Equivalent On-Resistance
- $h_{FE}$  Specified Up to 3A for a High Gain Hold-Up
- Complementary PNP Type: NK-FZT957Q


## Mechanical Data

- Package: SOT223
- Package Material: Molded Plastic. "Green" Molding Compound. UL Flammability Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish - Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208 (E3)
- Weight: 0.112 grams (Approximate)


SOT223



Top View



Device Symbol



Top View  
Pin-Out

**Absolute Maximum Ratings** (@  $T_A = +25^{\circ}\text{C}$ , unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	$V_{CBO}$	350	V
Collector-Emitter Voltage	$V_{CEO}$	300	V
Emitter-Base Voltage	$V_{EBO}$	7	V
Continuous Collector Current	$I_C$	3.5	A
Peak Pulse Current	$I_{CM}$	5	A

**Thermal Characteristics** (@  $T_A = +25^{\circ}\text{C}$ , unless otherwise specified.)


Characteristic	Symbol	Value	Unit
Power Dissipation Linear Derating Factor	$P_D$	3.0	W
		24	
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	1.6	mW/ $^{\circ}\text{C}$
		12.8	
Thermal Resistance Junction to Lead	$R_{\theta JL}$	42	$^{\circ}\text{C}/\text{W}$
		78	
Operating and Storage Temperature Range	$T_J, T_{STG}$	-55 to +150	$^{\circ}\text{C}$

**ESD Ratings** (Note 8)


Characteristic	Symbol	Value	Unit	JEDEC Class
Electrostatic Discharge - Human Body Model	ESD HBM	8,000	V	3B
Electrostatic Discharge - Machine Model	ESD MM	400	V	C

- Notes:
- For a device mounted with the collector lead on 52mm x 52mm 2oz copper that is on a single-sided 1.6mm FR4 PCB; device is measured under still air conditions whilst operating in steady-state.
  - Same as Note 6, except the device is mounted on 25mm x 25mm 1oz copper.
  - Thermal resistance from junction to solder-point (at the end of the collector lead).
  - Refer to JEDEC specification JESD22-A114 and JESD22-A115.


## Thermal Characteristics and Derating Information




**Safe Operating Area**



**Derating Curve**



**Transient Thermal Impedance**









**Pulse Power Dissipation**

**Electrical Characteristics** (@  $T_A = +25^\circ\text{C}$ , unless otherwise specified.)


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Collector-Base Breakdown Voltage	$BV_{CBO}$	350	475	—	V	$I_C = 100\mu\text{A}$
Collector-Emitter Breakdown Voltage	$BV_{CER}$	350	475	—	V	$I_C = 1\mu\text{A}$ , $R_B \leq 1\text{k}\Omega$
Collector-Emitter Breakdown Voltage (Note 9)	$BV_{CEO}$	300	350	—	V	$I_C = 1\text{mA}$
Emitter-Base Breakdown Voltage	$BV_{EBO}$	7	8	—	V	$I_E = 100\mu\text{A}$
Collector Cut-Off Current	$I_{CBO}$	—	1	50	nA $\mu\text{A}$	$V_{CB} = 300\text{V}$ $V_{CB} = 300\text{V}$ , $T_A = +100^\circ\text{C}$
Collector Cut-Off Current	$I_{CER}$	—	1	50	nA $\mu\text{A}$	$V_{CE} = 300\text{V}$ , $R_B \leq 1\text{k}\Omega$ $V_{CE} = 300\text{V}$ , $T_A = +100^\circ\text{C}$
Emitter Cut-Off Current	$I_{EBO}$	—	1	10	nA	$V_{EB} = 6\text{V}$
DC Current Gain (Note 9)	$h_{FE}$	100	200	—	—	$I_C = 10\text{mA}$ , $V_{CE} = 5\text{V}$
		100	200	300		$I_C = 500\text{mA}$ , $V_{CE} = 10\text{V}$
		15	25	—		$I_C = 2\text{A}$ , $V_{CE} = 10\text{V}$
		—	15	—		$I_C = 3\text{A}$ , $V_{CE} = 10\text{V}$
Collector-Emitter Saturation Voltage (Note 9)	$V_{CE(sat)}$	—	59	100	mV	$I_C = 500\text{mA}$ , $I_B = 50\text{mA}$
		—	95	155		$I_C = 1\text{A}$ , $I_B = 100\text{mA}$
		—	180	230		$I_C = 2\text{A}$ , $I_B = 200\text{mA}$
		—	300	345		$I_C = 3.5\text{A}$ , $I_B = 600\text{mA}$
Base-Emitter Saturation Voltage (Note 9)	$V_{BE(sat)}$	—	1,020	1,250	mV	$I_C = 3.5\text{A}$ , $I_B = 600\text{mA}$
Base-Emitter Turn-On Voltage (Note 9)	$V_{BE(on)}$	—	940	1,120	mV	$I_C = 3.5\text{A}$ , $V_{CE} = 10\text{V}$
Current Gain-Bandwidth Product (Note 9)	$f_T$	—	80	—	MHz	$I_C = 100\text{mA}$ , $V_{CE} = 10\text{V}$ , $f = 50\text{MHz}$
Output Capacitance	$C_{obo}$	—	21	—	pF	$V_{CB} = 20\text{V}$ , $f = 1\text{MHz}$
Switching Times	$t_{on}$	—	100	—	ns	$I_C = 250\text{mA}$ , $V_{CC} = 50\text{V}$ , $I_{B1} = -I_{B2} = 25\text{mA}$
	$t_{off}$	—	5,300	—		

 Note: 9. Measured under pulsed conditions. Pulse width  $\leq 300\mu\text{s}$ . Duty cycle  $\leq 2\%$ .

**Typical Electrical Characteristics** (@  $T_A = +25^\circ\text{C}$ , unless otherwise specified.)




### Package Outline Dimensions



SOT223 (Type DN)			
Dim	Min	Max	Typ
A	--	1.70	--
A1	0.01	0.15	--
A2	1.50	1.68	1.60
b	0.60	0.80	0.70
b2	2.90	3.10	--
c	0.20	0.32	--
D	6.30	6.70	--
E	6.70	7.30	--
E1	3.30	3.70	--
e	--	--	2.30
e1	--	--	4.60
L	0.85	--	--
All Dimensions in mm			

### Suggested Pad Layout



Dimensions	Value (in mm)
C	2.30
C1	6.40
X	1.20
X1	3.30
Y	1.60
Y1	1.60
Y2	8.00