



YOUSHANG SEMICONDUCTOR

**设计研发新型功率器件**

**各类小信号开关**

**中低压及高压大电流等场效应管**

0755-83047638  
ysbdt@szyoushang.cn  
www.szyoushang.cn



企业微信二维码



企业QQ二维码

## Features




- $BV_{CEX} > 100V$
- $BV_{CEO} > 20V$
- $BV_{ECO} > 6V$
- $I_C = 7A$  High Continuous Current
- Low Saturation Voltage  $V_{CE(sat)} < 48mV @ 1A$
- $R_{CE(sat)} = 31m\Omega$
- Complementary PNP Type: NK-ZXTP25020DG

## Mechanical Data

- Case: SOT223
- Case Material: Molded Plastic, "Green" Molding Compound;
- UL Flammability Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish - Matte Tin Plated Leads; Solderable per MIL-STD-202, Method 208  $\text{\textcircled{3}}$
- Weight: 0.112 grams (Approximate)

## Applications

- DC-DC Converters
- Motor Drive
- Relay, Lamp and Solenoid Drive
- Regulator Circuits



### Absolute Maximum Ratings

 (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	$V_{CBO}$	100	V
Collector-Emitter Voltage (forward blocking)	$V_{CEX}$	100	V
Collector-Emitter Voltage	$V_{CEO}$	20	V
Emitter-Collector Voltage (reverse blocking)	$V_{ECO}$	6	V
Emitter-Base Voltage	$V_{EBO}$	7	V
Continuous Collector Current	$I_C$	7	A
Base Current	$I_B$	1	A
Peak Pulse Current	$I_{CM}$	15	A

### Thermal Characteristics

 (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Power Dissipation Linear Derating Factor	$P_D$	1.2	W mW/ $^\circ\text{C}$
		9.6	
		1.6	
		12.8	
		3	
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	24	$^\circ\text{C/W}$
		5.3	
		42	
		104	
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	78	$^\circ\text{C/W}$
		42	
		23.5	
		16	
Thermal Resistance, Junction to Lead	$R_{\theta JL}$	16	$^\circ\text{C/W}$
Operating and Storage Temperature Range	$T_J, T_{STG}$	-55 to +150	$^\circ\text{C}$


### ESD Ratings

 (Note 10)


Characteristic	Symbol	Value	Unit	JEDEC Class
Electrostatic Discharge - Human Body Model	ESD HBM	4,000	V	3A
Electrostatic Discharge - Machine Model	ESD MM	400	V	C

- Notes:
- For a device mounted with the collector lead on 15mm x 15mm 1oz copper that is on a single-sided 1.6mm FR4 PCB; device is measured under still air conditions whilst operating in steady-state.
  - Same as Note 5, except the device is mounted on 25mm x 25mm 1oz copper.
  - Same as Note 5, except the device is mounted on 50mm x 50mm 2oz copper.
  - Same as Note 7 measured at  $t < 5$  seconds.
  - Thermal resistance from junction to solder-point (at the end of the collector lead).
  - Refer to JEDEC specification JESD22-A114 and JESD22-A115.


**Thermal Characteristics and Derating Information** (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)




**Safe Operating Area**




**Safe Operating Area**



**Transient Thermal Impedance**



**Pulse Power Dissipation**








**Derating Curve**

**Electrical Characteristics** (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Collector-Base Breakdown Voltage	$BV_{CBO}$	100	125	–	V	$I_C = 100\mu\text{A}$
Collector-Emitter Breakdown Voltage (forward blocking)	$BV_{CEX}$	100	120	–	V	$I_C = 100\mu\text{A}$ , $R_{BE} < 1\text{k}\Omega$ or $-1\text{V} < V_{BE} > 0.25\text{V}$
Collector-Emitter Breakdown Voltage (Note 11)	$BV_{CEO}$	20	35	–	V	$I_C = 10\text{mA}$
Emitter-Collector Breakdown Voltage (reverse blocking)	$BV_{ECX}$	6	8.3	–	V	$I_E = 100\mu\text{A}$ , $R_{BC} < 1\text{k}\Omega$ or $0.25\text{V} < V_{BC} > -0.25\text{V}$
Emitter-Collector Breakdown Voltage (reverse blocking)	$BV_{ECO}$	5	6.1	–	V	$I_E = 100\mu\text{A}$
Emitter-Base Breakdown Voltage	$BV_{EBO}$	7	8.3	–	V	$I_E = 100\mu\text{A}$
Collector Cut-Off Current	$I_{CBO}$	–	< 1	50	nA	$V_{CB} = 100\text{V}$
		–	–	0.5	$\mu\text{A}$	$V_{CB} = 100\text{V}$ , $T_A = 100^\circ\text{C}$
Collector-Emitter Cut-Off Current	$I_{CEX}$	–	–	100	nA	$V_{CE} = 100\text{V}$ , $R_{BE} < 1\text{k}\Omega$ or $-1\text{V} < V_{BE} > 0.25\text{V}$
Emitter Cut-Off Current	$I_{EBO}$	–	< 1	50	nA	$V_{EB} = 5.6\text{V}$
Collector-Emitter Saturation Voltage (Note 11)	$V_{CE(sat)}$	–	40	48	mV	$I_C = 1\text{A}$ , $I_B = 100\text{mA}$
		–	60	75	mV	$I_C = 1\text{A}$ , $I_B = 20\text{mA}$
		–	100	120	mV	$I_C = 2\text{A}$ , $I_B = 40\text{mA}$
		–	130	180	mV	$I_C = 2\text{A}$ , $I_B = 20\text{mA}$
		–	225	290	mV	$I_C = 7\text{A}$ , $I_B = 700\text{mA}$
Base-Emitter Saturation Voltage (Note 11)	$V_{BE(sat)}$	–	1,090	1,150	mV	$I_C = 7\text{A}$ , $I_B = 700\text{mA}$
Base-Emitter Turn-On Voltage (Note 11)	$V_{BE(on)}$	–	950	1,050	mV	$I_C = 7\text{A}$ , $V_{CE} = 2\text{V}$
DC Current Gain (Note 11)	$h_{FE}$	300	450	900	–	$I_C = 10\text{mA}$ , $V_{CE} = 2\text{V}$
		250	360	–	–	$I_C = 2\text{A}$ , $V_{CE} = 2\text{V}$
		50	85	–	–	$I_C = 7\text{A}$ , $V_{CE} = 2\text{V}$
		–	15	–	–	$I_C = 15\text{A}$ , $V_{CE} = 2\text{V}$
Current Gain-Bandwidth Product (Note 11)	$f_T$	–	215	–	MHz	$V_{CE} = 10\text{V}$ , $I_C = 50\text{mA}$ , $f = 100\text{MHz}$
Input Capacitance (Note 11)	$C_{ibo}$	–	152	–	pF	$V_{EB} = 0.5\text{V}$ , $f = 1\text{MHz}$
Output Capacitance (Note 11)	$C_{obo}$	–	16.5	25	pF	$V_{CB} = 10\text{V}$ , $f = 1\text{MHz}$
Delay Time	$t_d$	–	67.7	–	ns	$I_C = 1\text{A}$ , $V_{CC} = 10\text{V}$ , $I_{B1} = -I_{B2} = 10\text{mA}$
Rise Time	$t_r$	–	72.2	–	ns	
Storage Time	$t_s$	–	361	–	ns	
Fall Time	$t_f$	–	63.9	–	ns	

 Note: 11. Measured under pulsed conditions. Pulse width  $\leq 300\mu\text{s}$ . Duty cycle  $\leq 2\%$ .

**Typical Electrical Characteristics** (@T<sub>A</sub> = +25°C, unless otherwise specified.)




### Package Outline Dimensions



SOT223			
Dim	Min	Max	Typ
A	1.55	1.65	1.60
A1	0.010	0.15	0.05
b	0.60	0.80	0.70
b1	2.90	3.10	3.00
C	0.20	0.30	0.25
D	6.45	6.55	6.50
E	3.45	3.55	3.50
E1	6.90	7.10	7.00
e	-	-	4.60
e1	-	-	2.30
L	0.85	1.05	0.95
Q	0.84	0.94	0.89
All Dimensions in mm			

### Suggested Pad Layout



Dimensions	Value (in mm)
C	2.30
C1	6.40
X	1.20
X1	3.30
Y	1.60
Y1	1.60
Y2	8.00