



YOUSHANG SEMICONDUCTOR

设计研发新型功率器件

各类小信号开关

中低压及高压大电流等场效应管

0755-83047638

ysbdt@szyoushang.cn

www.szyoushang.cn



企业微信二维码



企业QQ二维码

Features



- 3.2GHz unity gain for RF switching applications

Applications

- RF switch

Mechanical Data

- Case: SOT23
- Case material: molded plastic. "Green" molding compound.
- UL Flammability Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish - Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208 ③
- Weight: 0.008 grams (approximate)



Maximum Ratings (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)

| Characteristic | Symbol | Value | Unit |
|------------------------------|-----------|-------|------|
| Collector-Base Voltage | V_{CBO} | 20 | V |
| Collector-Emitter Voltage | V_{CEO} | 11 | V |
| Emitter-Base Voltage | V_{EBO} | 3 | V |
| Continuous Collector Current | I_C | 50 | mA |

Thermal Characteristics (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)


| Characteristic | Symbol | Value | Unit |
|---|-----------------|-----------------|--------------------|
| Power Dissipation | P_D | (Note 6) 310 | mW |
| | | (Note 7) 350 | |
| Thermal Resistance, Junction to Ambient | $R_{\theta JA}$ | (Note 6) 403 | $^\circ\text{C/W}$ |
| | | (Note 7) 357 | |
| Thermal Resistance, Junction to Leads | $R_{\theta JL}$ | 350 | $^\circ\text{C/W}$ |
| Operating and Storage Temperature Range | T_J, T_{STG} | -55 to +150 | $^\circ\text{C}$ |

ESD Ratings (Note 9)


| Characteristic | Symbol | Value | Unit | JEDEC Class |
|--|---------|-------|------|-------------|
| Electrostatic Discharge - Human Body Model | ESD HBM | 2,000 | V | 2 |
| Electrostatic Discharge - Machine Model | ESD MM | 100 | V | A |

- Notes:
6. For the device mounted on minimum recommended pad layout FR4 PCB with high coverage of single sided 1oz copper in still air condition;
 7. Same as Note 6, expect the device is mounted on 15mm X 15mm X 1.6mm FR4 PCB
 8. Thermal resistance from junction to solder-point (at the end of the leads).
 9. Refer to JEDEC specification JESD22-A114 and JESD22-A115.


Thermal Characteristics and Derating information



Derating Curve



Transient Thermal Impedance









Pulse Power Dissipation

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)


| Characteristic | Symbol | Min | Typ | Max | Unit | Test Condition |
|---|---------------|-----|-----|-----|---------|---------------------------------------|
| Collector-Base Breakdown Voltage | BV_{CBO} | 20 | – | – | V | $I_C = 10\mu A$ |
| Collector-Emitter Breakdown Voltage (Note 10) | BV_{CEO} | 11 | – | – | V | $I_C = 1mA$ |
| Emitter-Base Breakdown Voltage | BV_{EBO} | 3 | – | – | V | $I_E = 10\mu A$ |
| Collector Cutoff Current | I_{CBO} | – | – | 0.5 | μA | $V_{CB} = 10V$ |
| Emitter Cutoff Current | I_{EBO} | – | – | 0.5 | μA | $V_{EB} = 2V$ |
| Static Forward Current Transfer Ratio (Note 10) | h_{FE} | 56 | – | 180 | – | $I_C = 5mA, V_{CE} = 10V$ |
| Collector-Emitter Saturation Voltage (Note 10) | $V_{CE(sat)}$ | – | – | 0.5 | V | $I_C = 25mA, I_B = 5mA$ |
| Transition Frequency (Note 10) | f_T | 1.4 | 3.2 | – | GHz | $I_E = 25mA, V_{CE} = 5V, f = 500MHz$ |
| Collector Output Capacitance (Note 10) | C_{ob} | – | 0.8 | 1.5 | pF | $V_{CB} = 10V, f = 1MHz$ |

 Notes: 10. Measured under pulsed conditions. Pulse width $\leq 300\mu s$. Duty cycle $\leq 2\%$

Typical Electrical Characteristics (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)




Package Outline Dimensions



| SOT23 | | | |
|----------------------|-------|------|-------|
| Dim | Min | Max | Typ |
| A | 0.37 | 0.51 | 0.40 |
| B | 1.20 | 1.40 | 1.30 |
| C | 2.30 | 2.50 | 2.40 |
| D | 0.89 | 1.03 | 0.915 |
| F | 0.45 | 0.60 | 0.535 |
| G | 1.78 | 2.05 | 1.83 |
| H | 2.80 | 3.00 | 2.90 |
| J | 0.013 | 0.10 | 0.05 |
| K | 0.903 | 1.10 | 1.00 |
| K1 | - | - | 0.400 |
| L | 0.45 | 0.61 | 0.55 |
| M | 0.085 | 0.18 | 0.11 |
| α | 0° | 8° | - |
| All Dimensions in mm | | | |

Suggested Pad Layout



| Dimensions | Value (in mm) |
|------------|---------------|
| Z | 2.9 |
| X | 0.8 |
| Y | 0.9 |
| C | 2.0 |
| E | 1.35 |