



YOUSHANG SEMICONDUCTOR

**设计研发新型功率器件**

**各类小信号开关**

**中低压及高压大电流等场效应管**

0755-83047638

ysbdt@szyoushang.cn

www.szyoushang.cn



企业微信二维码



企业QQ二维码

## Product Summary

| $BV_{DSS}$ | $R_{DS(on) Max}$          | $I_{D Max}$<br>$T_A = +25^\circ C$ |
|------------|---------------------------|------------------------------------|
| -50V       | $10\Omega @ V_{GS} = -5V$ | -130mA                             |

## Description and Applications

This MOSFET is designed to meet the stringent requirements of automotive applications. It is qualified to AEC-Q101, supported by a PPAP and is ideal for use in:

- General Purpose Interfacing Switch
- Power Management Functions
- Analog Switch




## Features and Benefits

- Low On-Resistance
- Low Gate Threshold Voltage
- Low Input Capacitance
- Fast Switching Speed

## Mechanical Data

- Case: SOT363
- Case Material: Molded Plastic. "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Matte Tin Finish Annealed over Alloy 42 Leadframe (Lead Free Plating). Solderable per MIL-STD-202, Method 208 
- Terminal Connections: See Diagram
- Weight: 0.006 grams (Approximate)



**Maximum Ratings** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Characteristic              | Symbol           | Value | Unit |
|-----------------------------|------------------|-------|------|
| Drain-Source Voltage        | V <sub>DSS</sub> | -50   | V    |
| Drain-Gate Voltage (Note 5) | V <sub>DGR</sub> | -50   | V    |
| Gate-Source Voltage         | V <sub>GSS</sub> | ±20   | V    |
| Drain Current (Note 6)      | I <sub>D</sub>   | -130  | mA   |

**Thermal Characteristics** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Characteristic                          | Symbol                            | Value       | Unit |
|---|-----------------------------------|-------------|------|
| Total Power Dissipation (Note 6)        | P <sub>D</sub>                    | 300         | mW   |
| Thermal Resistance, Junction to Ambient | R <sub>θJA</sub>                  | 417         | °C/W |
| Operating and Storage Temperature Range | T <sub>J</sub> , T <sub>STG</sub> | -55 to +150 | °C   |

**Electrical Characteristics** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Characteristic                            | Symbol              | Min  | Typ  | Max  | Unit | Test Condition  |
|---|---------------------|------|------|------|------|---|
| <b>OFF CHARACTERISTICS (Note 7)</b>       |                     |      |      |      |      |   |
| Drain-Source Breakdown Voltage            | BV <sub>DSS</sub>   | -50  | -75  | —    | V    | V <sub>GS</sub> = 0V, I <sub>D</sub> = -250μA                         |
| Zero Gate Voltage Drain Current           | I <sub>DSS</sub>    | —    | —    | -1   | μA   | V <sub>DS</sub> = -50V, V <sub>GS</sub> = 0V, T <sub>J</sub> = +25°C  |
|   |                     | —    | —    | -2   | μA   | V <sub>DS</sub> = -50V, V <sub>GS</sub> = 0V, T <sub>J</sub> = +125°C |
|   |                     | —    | —    | -100 | nA   | V <sub>DS</sub> = -25V, V <sub>GS</sub> = 0V, T <sub>J</sub> = +25°C  |
| Gate-Body Leakage                         | I <sub>GSS</sub>    | —    | —    | ±10  | nA   | V <sub>GS</sub> = ±20V, V <sub>DS</sub> = 0V                          |
| <b>ON CHARACTERISTICS (Note 7)</b>        |                     |      |      |      |      |   |
| Gate Threshold Voltage                    | V <sub>GS(th)</sub> | -0.8 | -1.6 | -2.0 | V    | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = -1mA             |
| Static Drain-Source On-Resistance         | R <sub>DS(ON)</sub> | —    | 6    | 10   | Ω    | V <sub>GS</sub> = -5V, I <sub>D</sub> = -0.1A                         |
| Forward Transconductance                  | g <sub>FS</sub>     | 0.05 | —    | —    | S    | V <sub>DS</sub> = -25V, I <sub>D</sub> = -0.1A                        |
| <b>DYNAMIC CHARACTERISTICS (Note 8)</b>   |                     |      |      |      |      |   |
| Input Capacitance                         | C <sub>iss</sub>    | —    | —    | 45   | pF   | V <sub>DS</sub> = -25V, V <sub>GS</sub> = 0V, f = 1.0MHz              |
| Output Capacitance                        | C <sub>oss</sub>    | —    | —    | 25   | pF   |   |
| Reverse Transfer Capacitance              | C <sub>rss</sub>    | —    | —    | 12   | pF   |   |
| <b>SWITCHING CHARACTERISTICS (Note 8)</b> |                     |      |      |      |      |   |
| Turn-On Delay Time                        | t <sub>D(ON)</sub>  | —    | 10   | —    | ns   | V <sub>DD</sub> = -30V, I <sub>D</sub> = -0.27A,                      |
| Turn-Off Delay Time                       | t <sub>D(OFF)</sub> | —    | 18   | —    | ns   | R <sub>GEN</sub> = 50Ω, V <sub>GS</sub> = -10V                        |




Fig. 1 Max Power Dissipation vs. Ambient Temperature




Fig. 2 Drain-Source Current vs. Drain-Source Voltage




Fig. 3 Drain-Current vs. Gate-Source Voltage




Fig. 4 On-Resistance vs. Gate-Source Voltage




Fig. 5 On-Resistance vs. Junction Temperature





Fig. 6 On-Resistance vs. Drain-Current

## Package Outline Dimensions


SOT363



| SOT363               |           |      |       |
|----------------------|-----------|------|-------|
| Dim                  | Min       | Max  | Typ   |
| A1                   | 0.00      | 0.10 | 0.05  |
| A2                   | 0.90      | 1.00 | 0.95  |
| b                    | 0.10      | 0.30 | 0.25  |
| c                    | 0.10      | 0.22 | 0.11  |
| D                    | 1.80      | 2.20 | 2.15  |
| E                    | 2.00      | 2.20 | 2.10  |
| E1                   | 1.15      | 1.35 | 1.30  |
| e                    | 0.650 BSC |      |       |
| F                    | 0.40      | 0.45 | 0.425 |
| L                    | 0.25      | 0.40 | 0.30  |
| a                    | 0°        | 8°   | --    |
| All Dimensions in mm |           |      |       |

## Suggested Pad Layout

SOT363



| Dimensions | Value (in mm) |
|------------|---------------|
| C          | 0.650         |
| G          | 1.300         |
| X          | 0.420         |
| Y          | 0.600         |
| Y1         | 2.500         |