



YOUSHANG SEMICONDUCTOR

设计研发新型功率器件

各类小信号开关

中低压及高压大电流等场效应管

0755-83047638

ysbdt@szyoushang.cn

www.szyoushang.cn



企业微信二维码



企业QQ二维码


Features

- < Low On-Resistance
- < Low Gate Threshold Voltage $V_{GS(th)} < 1V$
- < Low Input Capacitance
- < Fast Switching Speed
- < Low Input/Output Leakage
- < Complementary Pair MOSFET
- < Ultra-Small Surface Mount Package
- < ESD Protected Gate

Mechanical Data

- < Case: X1-DFN1612-6
- < Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- < Moisture Sensitivity: Level 1 per J-STD-020C
- < Terminal Connections: See Diagram
- < Terminals: Finish . NiPdAu over Copper leadframe. Solderable per MIL-STD-202, Method 208 **e4**
- < Weight: 0.003 grams (approximate)

X1-DFN1612-6



Maximum Ratings N-CHANNEL $\bar{E} Q_1$ (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Drain Source Voltage	V_{DSS}	20	V
Gate-Source Voltage	V_{GSS}	.8	V
Drain Current (Note 5)	I_D	$T_A = +25^\circ\text{C}$	750
		$T_A = +85^\circ\text{C}$	540

Maximum Ratings P-CHANNEL $-Q_2$ (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Drain Source Voltage	V_{DSS}	-20	V
Gate-Source Voltage	V_{GSS}	.8	V
Drain Current (Note 5)	I_D	$T_A = +25^\circ\text{C}$	-600
		$T_A = +85^\circ\text{C}$	-430

Thermal Characteristics (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 5)	P_D	500	mW
Thermal Resistance, Junction to Ambient	R_{JA}	250	$^\circ\text{C}/\text{W}$
Operating and Storage Temperature Range	T_J, T_{STG}	-65 to +150	$^\circ\text{C}$

Electrical Characteristics N-CHANNEL $\bar{E} Q_1$ (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 6)						
Drain-Source Breakdown Voltage	BV_{DSS}	20	.	.	V	$V_{GS} = 0V, I_D = 10\mu\text{A}$
Zero Gate Voltage Drain Current	I_{DSS}	.	.	1	μA	$V_{DS} = 16V, V_{GS} = 0V$
Gate-Source Leakage	I_{GSS}1	μA	$V_{GS} = \pm 4.5V, V_{DS} = 0V$
ON CHARACTERISTICS (Note 6)						
Gate Threshold Voltage	$V_{GS(th)}$	0.5	.	1.0	V	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$
Static Drain-Source On-Resistance	$R_{DS(on)}$.	0.4	0.55		$V_{GS} = 4.5V, I_D = 540\text{mA}$
		.	0.5	0.70		$V_{GS} = 2.5V, I_D = 500\text{mA}$
		.	0.7	0.90		$V_{GS} = 1.8V, I_D = 350\text{mA}$
Forward Transfer Admittance	$ Y_{fs} $	200	.	.	mS	$V_{DS} = 10V, I_D = 0.2A$
Diode Forward Voltage (Note 6)	V_{SD}	0.5	.	1.2	V	$V_{GS} = 0V, I_S = 115\text{mA}$
DYNAMIC CHARACTERISTICS						
Input Capacitance	C_{iss}	.	.	150	pF	$V_{DS} = 16V, V_{GS} = 0V$ $f = 1.0\text{MHz}$
Output Capacitance	C_{oss}	.	.	25	pF	
Reverse Transfer Capacitance	C_{rss}	.	.	20	pF	

Electrical Characteristics P-CHANNEL $\bar{E} Q_2$ (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 6)						
Drain-Source Breakdown Voltage	BV_{DSS}	-20	.	.	V	$V_{GS} = 0V, I_D = -250\mu\text{A}$
Zero Gate Voltage Drain Current	I_{DSS}	.	.	-1.0	μA	$V_{DS} = -20V, V_{GS} = 0V$
Gate-Source Leakage	I_{GSS}1.0	μA	$V_{GS} = \pm 4.5V, V_{DS} = 0V$
ON CHARACTERISTICS (Note 6)						
Gate Threshold Voltage	$V_{GS(th)}$	-0.5	.	-1.0	V	$V_{DS} = V_{GS}, I_D = -250\mu\text{A}$
Static Drain-Source On-Resistance	$R_{DS(on)}$.	0.7	0.9		$V_{GS} = -4.5V, I_D = -430\text{mA}$
		.	1.1	1.4		$V_{GS} = -2.5V, I_D = -300\text{mA}$
		.	1.7	2.0		$V_{GS} = -1.8V, I_D = -150\text{mA}$
Forward Transfer Admittance	$ Y_{fs} $	200	.	.	mS	$V_{DS} = 10V, I_D = 0.2A$
Diode Forward Voltage (Note 5)	V_{SD}	-0.5	.	-1.2	V	$V_{GS} = 0V, I_S = -115\text{mA}$
DYNAMIC CHARACTERISTICS						
Input Capacitance	C_{iss}	.	.	175	pF	$V_{DS} = -16V, V_{GS} = 0V$ $f = 1.0\text{MHz}$
Output Capacitance	C_{oss}	.	.	30	pF	
Reverse Transfer Capacitance	C_{rss}	.	.	20	pF	

- Notes:
- Device mounted on FR-4 PCB.
 - Short duration pulse test used to minimize self-heating effect.

Q1, N-CHANNEL




Fig. 1 Typical Output Characteristics




Fig. 2 Typical Transfer Characteristics




Fig. 3 Gate Threshold Voltage vs. Ambient Temperature




Fig. 4 Static Drain-Source On-Resistance vs. Drain Current




Fig. 5 Static Drain-Source On-Resistance vs. Drain Current




Fig. 6 Static Drain-Source On-Resistance vs. Drain-Source Current vs. Gate Source Voltage

Q₁, N-CHANNEL (continued)




Fig. 7 Static Drain-Source On-State Resistance vs. Ambient Temperature




Fig. 8 Drain Reverse Current vs. Source-Drain Voltage




Fig. 9 Forward Transfer Admittance vs. Drain Current




Fig. 10 Typical Capacitance

Q₂, P-CHANNEL




Fig. 11 Typical Output Characteristics




Fig. 12 Typical Transfer Characteristics




Fig. 13 Gate Threshold Voltage vs. Ambient Temperature




Fig. 14 Static Drain-Source On-Resistance vs. Drain Current




Fig. 15 Static Drain-Source On-Resistance vs. Drain Current




Fig. 16 Static Drain-Source On-Resistance vs. Drain-Source Current vs. Gate Source Voltage

Q₂, P-CHANNEL (continued)




Fig. 17 Static Drain-Source On-State Resistance vs. Ambient Temperature




Fig. 18 Drain Reverse Current vs. Source-Drain Voltage




Fig. 19 Forward Transfer Admittance vs. Drain Current






Fig. 20 Typical Capacitance

Package Outline Dimensions



X1-DFN1612-6			
Dim	Min	Max	Typ
A	0.47	0.53	0.50
A1	0	0.05	0.02
A3	-	-	0.13
b	0.15	0.25	0.20
D	1.55	1.675	1.60
d	-	-	0.25
D2	0.40	0.60	0.50
E	1.15	1.28	1.20
e	-	-	0.40
E2	0.45	0.65	0.55
f	-	-	0.15
L	0.20	0.30	0.25
Z	-	-	0.10
All Dimensions in mm			

Suggested Pad Layout



Dimensions	Value (in mm)
G1	0.15
G2	0.175
G3	0.15
X1	0.60
X2	0.25
Y1	0.65
Y2	0.45
a	0.10
b	0.15